



**AT 70**

**CLEAR “EZ-TEAR” APPLICATION FILM**

**BACKING**

An easy-to-tear, embossed transparent polyethylene-based film for transfer of die-cut and computer-cut letters and emblems.

**ADHESIVE**

A modified acrylic adhesive designed for clean pick up and transfer performance on all brands of cast or calendared vinyl. The stable adhesive will not build in tack level when applied to vinyl graphics for extended periods of storage, therefore transfer is never a problem.

PHYSICAL SPECIFICATIONS	
Film	145mµ embossed polyethylene
Adhesive	Modified Polyacrylate
Color	Transparent
Total tape thickness (PSTC-33)	163mµ
*Adhesion to steel (PSTC-1)	4-6 N/25mm
Tensile (PSTC-31)	13 Mpa
Elongation	300- 500%
Tear resistance	50-70 grams
Application temperature	Min +10C°

*\*Adhesion PSTC-1, 1 minute on stainless steel at time of manufacture.*

**•FEATURES**

- Hand-tearable for easy dispensing
- Forgiving adhesive system! If the adhesive side of the film accidentally folds onto itself, it is easy to pull apart without delamination!
- Good clarity to aid precise registration of multi-color overlays.
- Easy unwind eliminates exhausting application tape struggles.
- Rigid polyethylene face stock minimizes misalignment problems.
- Excellent lay flat to resist curling.
- Unique adhesive system will not build to vinyl during storage of graphics.

**WARRANTY**

TAPES ARE ONLY WARRANTED TO BE FREE OF DEFECTS IN WORKMANSHIP OR MATERIAL AT TIME OF SHIPMENT. MANUFACTURER WILL REPLACE OR CREDIT ANY MATERIAL MANUFACTURER DEEMS DEFECTIVE. NO ACCEPTANCE OR RESPONSIBILITY FOR LOSS, DAMAGE, OR EXPENSE, IMPLIED OR OTHERWISE, SHALL BE ASSUMED BY SELLER OR MANUFACTURER. USER ASSUMES ALL RISK AND LIABILITY IN CONNECTION HEREWITH.

32-9-216 6709

sales@rtape.be 32-9-216 6700

R Tape Tech Data