

DATA SHEET

H999 1.0MM DOUBLE COATED CLEAR ACRYLIC FOAM

CHARACTERISTIC	VALUE
ADHESIVE	ACRYLIC
LINER	RED LOW DENSITY POLYETHYLENE FILM
CARRIER	ACRYLIC FOAM
ADHESIVE STRENGTH	29 N/25MM
DYNAMIC SHEAR	5 KG/CM ²
TOTAL THICKNESS	1.0 MM
SERVICE TEMPERATURE	-40°C TO +93°C
SHORT TERM TEMPERATURE	+150°C
RECOMMENDATIONS FOR USE	TEMPERATURE: BETWEEN +15°C AND +30°C SURFACE MUST BE CLEAN, DRY, DUST & GREASE FREE. INDICATED PERFORMANCE LEVEL ACHIEVED AFTER A BONDING PERIOD OF 24HRS AT +23°C
COLOUR	CLEAR
SHELF LIFE AND STORAGE	2 YEARS MINIMUM SUBJECT TO STORAGE IN A CLEAN, DRY, VENTILATED AREA AT BETWEEN +10°C & +30°C

PRODUCT FEATURES AND APPLICATIONS

A PERMANENT BONDING ACRYLIC FOAM TAPE FOR INTERIOR AND EXTERIOR USE.
EXCELLENT RESISTANCE TO SOLVENT, UV AND MOISTURE.
SUITABLE FOR MAKING A SECURE BOND TO A VERY WIDE RANGE OF SUBSTRATES.
IDEAL FOR BONDING SIGNS, EMBLEMS, NAMEPLATES AND METAL

THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE AND THE USER
ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

DATE OF ISSUE : JUNE 2021